






4" Square Boxes – 2-1/8" Deep

With Knockouts

UL Standard: 514A
 UL Listed: E2527
 NEMA: OS-1

	Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description			Wt. Lbs./Kgs. Per 100	
				Sides	Ends	Bottom		
 2-1/8" Deep, Welded	4SD-EK	2-1/8	30.3	(8) 1/2" (4) Eccentric KO	—	(2) 1/2" (2) Eccentric KO	82.0/ 37.19	
	4SD-EKRD *	Red Box Option	2-1/8	30.3	(8) 1/2" (4) Eccentric KO	—	(2) 1/2" (2) Eccentric KO	82.0/ 37.19
 2-1/8" Deep, Welded	4SD-EKP †	With Green Ground Wire	2-1/8	30.3	(8) 1/2" (4) Eccentric KO	—	(2) 1/2" (2) Eccentric KO	82.0/ 37.19
 2-1/8" Deep, Welded	4SD-3/4 (52171-3/4)		2-1/8	30.3	(8) 3/4"	—	(3) 1/2" (2) 3/4"	84.0/ 38.10
 2-1/8" Deep, Welded	4SD-1 (52171-1)		2-1/8	30.3	(8) 1"	—	(3) 1/2" (2) 3/4"	84.0/ 38.10
 2-1/8" Deep, Welded; Plain vertical bracket; Set flush with front of box	4SDVB-EK-PL		2-1/8	30.3	(6) 1/2" (3) Eccentric KO	—	(2) 1/2" (2) Eccentric KO	104.0/ 47.17
	4SDVB-EK-PLRD *	Red Box Option	2-1/8	30.3	(6) 1/2" (3) Eccentric KO	—	(2) 1/2" (2) Eccentric KO	104.0/ 47.17

* For fire alarm circuits. Red powder coat finish.

† Provided with green ground screw and 10" long No. 12 AWG solid, insulated green ground wire.