



BURNDY Catalog Number	BIBD2505
UPC Number	781810133422
Description	250-10, 2-SIDE,UNI-TAP
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Width (in)	2.64
Hex Size (Key)	5/16
Length (in)	4.84
Height (in)	2.13

Electrical	
Min Voltage Rating	600

General	
Number of Ports	5
Number of Screws	5

Product Description	Aluminum Multiple Tap Connector, Clear Insulated, 5 Port, 2 Sided Entry, 10 AWG-250 kcmil, Al/Cu Rated
---------------------	--

Conductor(s)	
Aluminum Size (Range)	8 AWG-250 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	10 AWG-250 kcmil

Physical	
Type of Hardware	Aluminum
Type of Plating	Unplated
Insulation Type	Plastisol
Plated (Yes or No)	N
Product Material	Aluminum

Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175