



# Blackburn®

## Split-Bolt

T&B Catalog Number:

1H3

UPC Number:

78378620013

Status:

Active

Description:

Type H High Strength Split-Bolt Connector, Bronze Alloy for Use on Copper Conductors, Conductor Range for Equal Main and Tap 2 Str-6 Sol

### Features

Bolt and nut of high-strength corrosion-resistant bronze alloy. Copper pressure bar. Bolt and nut of hex design.

### Standards

UL, CSA

### Application

Splicing, tapping or terminating conductors in power and grounding electrical connection.

### General

Style	Type H
Wire Type	Copper
Material	Bronze Alloy
Color	Metallic
Conductor Range for Equal Main and Tap 2 Str.-6 Sol.	
Conductor Range Min. Tap with one Max. 14 Sol.	
Main	

### Dimension Information

A (inches)	11/16
B (inches)	0.330
C (inches)	7/8
D (inches)	1 5/8

### Packaging

T&B Inner Pack	100
Package in Units	400
T&B Sold in UOM	Each
T&B Weight Per UOM	13 lbs. per 100

### Notes

Will accommodate 3 #2 stranded wires.

The H3 bolts are not UL Listed or CSA Certified.

UL recognizes solid and stranded conductor configurations for sizes #8 and smaller and stranded configurations only for sizes #6 and larger.

### Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Memphis, TN 38125  
www.tnb.com

8155 T&B Blvd.  
Memphis, TN 38125

Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com