



Catamount®

Miniature

T&B Catalog Number:

L-4-18-0-M

UPC Number:

72849491450

Status:

Active

Description:

Miniature Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 100.08mm (3.94 Inches), Width of 2.41mm (0.095 Inches), Thickness of 1.13mm (0.045 Inches), Tensile Strength Rating of 80 Newtons (18 Pounds), Bulk Pack

General

| | |
|----------|-----------------------------|
| Material | Nylon 6.6 Weather Resistant |
| Color | Black |

Dimension Information

| | |
|------------------------------------|-------|
| Nominal Length (inches) | 4 |
| Length (inches) | 4.0 |
| Width (inches) | 0.100 |
| Max. Wire Bundle Diameter (inches) | 5/8 |
| Min. Wire Bundle Diameter (inches) | 1/16 |

Specifications

| | |
|----------------------------|----------------|
| Military Standard Part No. | MS-3367-4-0 |
| Temperature Rating | -40°F to 185°F |
| Flammability Rating | UL 94 V-2 |

Tooling

| | |
|-------------------|-------------------------------|
| Application Tools | ERG50, QC-100, L-200, L-400-C |
|-------------------|-------------------------------|

Packaging

| | |
|--------------------|--------------------|
| T&B Order Multiple | 1000 |
| T&B Inner Pack | 1000 |
| Package in Units | 25000 |
| Package Type | Bulk |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 0.66 lbs. per 1000 |

Application Support

| | |
|--------------------------|----------------------|
| T&B Sales Drawings | wsd-000218 |
| Overview | Available on Website |
| Material Selection Guide | Available on Website |
| Available Colors | Available on Website |

Certifications



For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321

Email:techsupport@tnb.com