

# XLERATOR® HAND DRYER



ORIGINAL. PATENTED. STILL THE BEST.

## NEW ENHANCED STANDARD FEATURES



Adjustable Speed and  
Sound Control



Multi-Voltage Options:  
110-120V Or 208-277V



Adjustable Heat Settings -  
High, Medium, Low & Off



Externally Visible  
Service LED

**8**

**SECONDS\***  
dry time

**95%**

**COST SAVINGS**  
versus paper towels

**80%**

**LESS ENERGY**  
than conventional dryers



# XLERATOR® HAND DRYER



MODELS: **XL - BW** **W** **GR** **C** **SB** **SI** **SP** OPTIONS: **-1.1N** (Noise Reduction Nozzle) **-H** (HEPA Filter) **-VOLTAGE** (See Chart)



**XL-BW**

White Thermoset Resin (BMC)



**XL-W**

White Epoxy Painted



**XL-GR**

Graphite Textured Painted



**XL-SP\*\***

Custom Special Paint



**XL-SI\*\*\***

Custom Special Image



**XL-C**

Chrome Plated



**XL-SB**

Brushed Stainless Steel

**TESTED TO PCR GUIDELINES** **DRY TIME: 8 SECONDS\*** **ENERGY PER USE: 3.7 Wh**

## FEATURES & BENEFITS

- ✓ 80% Less Energy Than Conventional Hand Dryers
- ✓ 95% Cost Savings Vs. Paper Towels
- ✓ Made In USA Certified®
- ✓ 5-Year Limited Warranty
- ✓ Building Green Approved and Helps Qualify for several LEED® credits
- ✓ A Hygienic Hand Drying Solution

## OPTIONS

- ✓ **HEPA Filtration System:** Filters 99.97% of bacteria at 0.3 microns from the air stream.
- ✓ **1.1 Noise Reduction Nozzle:** Lowers decibel level 9 dB by reducing air deflection noise but increases dry time by approximately 3 seconds.

## ONLINE INFORMATION

- ▶ Product Videos
- 💰 Cost Savings & Carbon Footprint Calculator
- 📊 Life Cycle Assessment Study
- 📘 Specification Tools
- 📄 AIA/GBCI CEU Courses
- 📄 Case Studies

## DIMENSIONS

**Width** 11 3/4" (298 mm) **Height** 12 11/16" (322 mm) **Depth** 6 11/16" (170 mm)

## WEIGHT

**XL-BW:** 15 lbs. (6.8 kgs.) **XL-SB:** 16 lbs. (7.26 kgs.) **XL-W, GR, C, SI, SP:** 17 lbs. (7.71 kgs.)

## ELECTRICAL

VOLTS	AMPS	WATTS	NO HEAT AMPS	NO HEAT WATTS	HERTZ	
110-120V	11.3-12.2A	1240-1450W	4.3-4.5A	460-530W	50/60 Hz	cUL US
208-277V	5.6-6.2A	1160-1490W	2.0-2.2A	425-500W	50/60 Hz	cUL US
230V	6.1A	1410W	2.2A	500W	50 Hz	CE



RoHS



## ACTIVATION

**Automatic Sensor Operated**

## MOUNTING

**Surface Mounted**

## SUGGESTED MOUNTING HEIGHTS

**Men** 45" (114 cm) **Women** 43" (109 cm) **Accessible** 37" (94 cm)

Note: Heights measured from floor to bottom of dryer.

## ACCESSORIES

- ✓ Anti-Microbial Wall Guards
- ✓ XChanger Paper Towel Dispenser Retrofit Kit
- ✓ ADA-Compliant Recess Kit

**Width** 16 3/8" (416 mm) **Height** 26" (660 mm)  
**Depth** 3 3/8" (86 mm) **Weight** 11 lbs. (4.99 kgs.)



**Part # 40502**

\* Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.

\*\* Special Paint powder-coated covers are available in many colors and textures.

\*\*\* Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.



UL Environment published the first global Product Category Rules (PCR) for Hand Dryers and Excel Dryer is proud to have been selected to chair the project. The PCR created evaluation methods through industry consensus that compare products' environmental impact and performance. Third party testing results then enable specifiers and buyers to make a true apples-to-apples comparison of products and more informed decisions.



# TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

JAN 2017

16XLS0001