HUBBELL Large Capacity Wall Box

- Designed to deliver power and low voltage in the same box
- Use standard wallplates
- Two inch knockouts
- 3 ¼ Inch depth accomodates large cables and bend radii
- Three raised ground screws

The Hubbell Large Capacity Wall Boxes are the ideal solution for in wall applications requiring AV, data and power. Concentric 1 inch – 2 inch knockouts plus large box volumes facilitate easy installation of AV cables incorporating pre-connectorized heads and bend radius required for high performance Category 6 and 6A cables.

The HBL260 (66.7 cu. in.) accepts industry standard 411/16 inch mud rings and the HBL263 (113.3 cu. in.) accepts industry standard 4 inch mud rings allowing them to be used in one- or two-gang applications. Additionally the HBL263 accepts Hubbell made mud rings for three-gang applications in a variety of wall thicknesses. All mud rings accommodate standard wall plates.

The UL listed **HBL981** low voltage partition is common to both boxes and is adjustable for multiple mud ring depths.

FEATURES HBL260 and HBL263 LARGE CAPACITY WALL BOX

- Knockouts from ½ inch up to 2 inch
- Accept HBL981 UL, listed, low voltage partition
- Raised ground provisions

HBL260 LARGE CAPACITY WALL BOX

- One- or two-gang wiring capacity, mud ring defines number of gangs
- 66.7 cubic inches of wiring capacity

HBL263 LARGE CAPACITY WALL BOX

- One-, two- or three-gang wiring capacity, mud ring defines number of gangs
- 113.3 Cubic inches of wiring capacity
- Built in stud mounting brackets
- Includes spanner strap tabs







Large Capacity Wall Box (66.7 cu. in.)





SPECIFICATIONS

- 31/4 inch depth
- Combination cover screws
- 2 inch knockouts

STANDARDS/LISTINGS/VERIFICATIONS

cULus

Two-Gang Large Capacity Wall Box

66.7 Cubic Inch Capacity

Description	Dimensions	Knockouts Sides*	Knockouts Back*	Catalog Number
Square 2-gang wall box	4 ¹¹ / ₁₆ "H x 4 ¹¹ / ₁₆ "W x 3½"D	(2) 3/4" - 1" TKO; (2) 1" - 11/4" TKO; (2) 1" - 2" conc. KO	(2) ¾" – 1" TKO (2) ½" TKO	HBL260

Note: Use with industry standard 411/16" square mud rings for 1- or 2-gang applications. * TKO (Tangential Knockout)

2-Gang Mud Rings - Compatible with HBL260

Description	Capacity (cu. in.)	Catalog Number
%" height	7.3	HBL818
3/4" height	8.8	HBL840
1" height	12.0	HBL819
11/4" height	15.0	HBL820

Three-Gang Large Capacity Wall Box

113.3 Cubic Inch Capacity

Description	Dimensions	Knockouts Sides	Knockouts Back	Catalog Number
Square 2- or 3-gang wall box	411/16"H x 73/4"W x 31/4"D	(4) ½" – ¾" TKO, (4) ¾" – 1" TKO, (2) 1" – 1¼" TKO, (2) 1" – 2" conc. KO	(2) ½" – ¾" TKO, (2) ¾" – 1" TKO, (2) 1" – 1¼" TKO	HBL263

Note: Use with industry standard 4" square mudrings for 1- or 2-gang applications.

3-Gang Mud Rings - Compatible with HBL263

Description	Capacity (cu. in.)	Catalog Number
½" height	10.1	HBL792
%" height	12.3	HBL793
1¼" height	24.3	HBL794



-ront Back



Front Back

Note: Cutaway images are for demonstration purposes only.

Accessories

Low Voltage Partition

Description Compatible with		Compatible Mud Ring Depth	Packing Quantity	Catalog Number
Low voltage partition	HBL260 and HBL263	½", ¾" and 1¼"	1	HBL981

Wallplates

manplatee					
Color	2-Gang, 2 Decorator	3-Gang, 3 Decorator	Material	2-Gang, 2 Decorator	3-Gang, 3 Decorator
Almond Black Brown Gray Ivory Light Almond	NP262AL NP262BK NP262 NP262GY NP262I NP262LA	NP263AL NP263BK NP263 NP263GY NP263I NP263LA	Brass Brass Plated Chrome S/S 302/304 S/S 430 Steel, Almond	SB262 SBP262 SCH262 SS262 SS262L PHPS2AL*	SBP263 SS263 PHPS3AL*
Office White Red White	NP262OW NP262R NP262W	NP263OW NP263R NP263W	Steel, Gray	PHPS2G*	_

^{*}Powder coat paint finish.



HBL260





HBL981



NP263I









www.hubbell-wiring.com

