

Technical Data  
**Horsepower Ratings**  
 For NEMA Configuration



**Horsepower Ratings for NEMA Configurations – Plugs and Receptacles Only**

Straight Blade		Locking	
NEMA Configuration	AC HP Rating <sup>1</sup>	NEMA Configuration	AC HP Rating <sup>1</sup>
1-15	0.5	L1-15	0.5
2-15	1.5*	L2-20	2*
2-20	2*	L5-15	0.5
2-30	2*	L5-20	1
5-15	0.5	L5-30	2
5-20	1	L6-15	1.5*
5-30	2	L6-20	2*
5-50	2	L6-30	2*
6-15	1.5*	L7-15	2
6-20	2*	L7-20	2
6-30	2*	L7-30	3
6-50	3*	L8-20	3
7-15	2	L8-30	5
7-20	2	L10-20	2 L-L*
7-30	3		1 L-N
7-50	5	L10-30	2 L-L*
10-20	2 L-L*		2 L-N
10-30	1 L-N	L11-15	2
	2 L-L*	L11-20	3
10-50	2 L-N	L11-30	3
	3 L-L*	L12-20	5
	2 L-N	L12-30	10
11-15	2	L14-20	2 L-L*
11-20	3		1 L-N
11-30	3	L14-30	2 L-L*
11-50	7.5		2 L-N
14-15	1.5 L-L*	L15-20	3
	0.5 L-N	L15-30	3
14-20	2 L-L*	L16-20	5
	1 L-N	L16-30	10
14-30	2 L-L*	L18-20	2
	2 L-N	L18-30	3
14-50	3 L-L*	L19-20	5
	2 L-N	L19-30	10
14-60	3 L-L*	L21-20	2
	2 L-N	L21-30	3
15-15	2	L22-20	5
15-20	3	L22-30	10
15-30	3		
15-50	7.5		
15-60	10		
18-15	2		
18-20	2		
18-30	3		
18-50	7.5		
18-60	7.5		

Note: <sup>1</sup>The phase to phase horsepower ratings are noted "L-L". The phase to neutral ratings are identified "L-N".  
 \* Also suitable for 208V.

