



T&B[®]

Rigid/IMC Conduit Fittings T&B Catalog Number:

UPC Number: 142-TB
78621000142
Status: Active
Description:

3/4 in. Steel locknut. For use with Rigid/IMC conduit.

Features

Hardened steel, malleable iron, copper-free aluminum construction
Tightens without deformation

Application

To connect externally threaded conduit or connector to a threadless opening in a box or enclosure.
To effectively bond conduit or connector to box or enclosure.

General

Material Steel

Dimension Information

Size (inches) 3/4
Dimension A (inches) 1 3/8
Dimension B (inches) 3/16

Specifications

3dmodel Available on Website

Packaging

T&B Order Multiple 100
T&B Inner Pack 100
Package in Units 1000
T&B Sold in UOM Each
T&B Weight Per UOM 2.2 lbs. per 100

Application Support

304 Stainless Steel Corrosion Compatibility Chart Available on Website
Product Overview Available on Website

Notes

Case hardened locknuts.

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com