



T&B®

Liquidtight Flexible Metal Conduit Fittings
T&B Catalog Number:

UPC Number: 5252
 78621005252
Status: Active
Description:

1/2 in. 90 degree malleable iron liquidtight connector

Features

Ability to install quickly with low torque effort

Application

Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

General

| | |
|---------------------|--------------------------------------|
| Trade Size (inches) | 1/2 |
| Material | Malleable Iron |
| Finish | Electro Zinc Plated/Chromate Coating |

Dimension Information

| | |
|----------------------|--------|
| Dimension A (inches) | 1 3/8 |
| Dimension B (inches) | 1 9/16 |
| Dimension C (inches) | 9/16 |

Specifications

3dmodel Available on Website

Accessories & Components

Wiremesh Grips for Liquidtight Fittings WMG-LT2

Packaging

| | |
|--------------------|-------------------|
| T&B Inner Pack | 25 |
| Package in Units | 50 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 29.5 lbs. per 100 |

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
 E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

