



T&B[®]

Liquidtight Flexible Metal Conduit Fittings T&B Catalog Number:

UPC Number: 5333
78621005333
Status: Active
Description:

3/4 in. straight steel insulated liquidtight connector

Features

Ability to install quickly with low torque effort

Application

Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

General

Trade Size (inches)	3/4
Material	Steel
Finish	Electro Zinc Plated/Chromate Coating

Dimension Information

Dimension A (inches)	1 21/32
Dimension B (inches)	1 5/8
Dimension C (inches)	9/16

Specifications

3dmodel Available on Website

Accessories & Components

Wiremesh Grips for Liquidtight Fittings WMG-LT3

Packaging

T&B Inner Pack	25
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	25.2 lbs. per 100

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321

