



T&B®

Rigid/IMC Conduit Fittings T&B Catalog Number:

UPC Number: H075TB
78621089604
Status: Active
Description:

3/4 in. Zinc Hub Connector with thermoplastic insulating throat; sealing ring-Nitrile (BUNA-N). For use with Rigid/IMC Conduit.

Application

Suitable for hazardous locations use in Class I, Division 2; Class II, Division 1&2; Class III, Division 1 & 2 per NEC 501-4(b); 502-4 (a) and 503-3 (a).
Suitable for hazardous locations use in Class II, Groups E, F, G & Class III locations per CEC 18-202; 18-252; 18-302; 18-352.

General

Trade Size (inches) 3/4
Material Zinc

Dimension Information

Dimension A (inches) 1 21/32
Dimension B (inches) 1 19/32
Dimension C (inches) 29/32
Dimension D (inches) 3/16
Dimension E (inches) 25/32

Specifications

3dmodel Available on Website

Packaging

T&B Inner Pack 25
Package in Units 100
T&B Sold in UOM Each
T&B Weight Per UOM 27.5 lbs. per 100

Application Support

Spacing Chart Available on Website

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125

T&B Technical Support
MS 3B-50
8155 T&B Blvd.

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289

