



T&B®

Rigid/IMC Conduit Fittings
T&B Catalog Number:

UPC Number: H150-TB
 78621050404
Status: Active
Description:

1 1/2 in. Zinc Hub Connector with thermoplastic insulating throat; sealing ring-Nitrile (BUNA-N). For use with Rigid/IMC Conduit.

Application

Suitable for hazardous locations use in Class I, Division 2; Class II, Division 1&2; Class III, Division 1 & 2 per NEC 501-4(b); 502-4 (a) and 503-3 (a).
 Suitable for hazardous locations use in Class II, Groups E, F, G & Class III locations per CEC 18-202; 18-252; 18-302; 18-352.

General

Trade Size (inches) 1-1/2
 Material Zinc

Dimension Information

Dimension A (inches) 2 3/4
 Dimension B (inches) 1 7/8
 Dimension C (inches) 1 1/16
 Dimension D (inches) 1/4
 Dimension E (inches) 1 17/32

Specifications

3dmodel Available on Website

Packaging

Package in Units 10
 T&B Sold in UOM Each
 T&B Weight Per UOM 62 lbs. per 100

Application Support

Spacing Chart Available on Website

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
 E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

