

## *Ty-Rap*°

**Standard T&B Catalog Number:** 

TY524M

**UPC Number:** 78621080605

Status: Active

**Description:** 

Cable Tie 30lb 5.5" Natural Nylon with Stainless Steel Locking Device

Application Tools

T&B Order Multiple

T&B Inner Pack

Package in Units

Package Type

**Packaging** 

Distributor Pack	With Stainless Steel Esching Device
Features	
	Oval low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. Because there are no notches, Ty-Rap ties provide an infinite number of locking positions while fastening the tie at the precise bundle diameter needed.
	The Turned-up Tail orients the tie for easy assembly, making the ties easier to pick up on a flat surface. The No-Slip Tail provides easy grip during tensioning. Ty-Rap ties feature a unique friction surface designed to reduce slippage during installation.
	Smooth, notchless body reduces stress concentration points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables.
General	
Material	Nylon 6.6
Color	Natural
Dimension Information	
Nominal Length (inches) Length (inches)	6 5.5
Width (inches)	.140
Max. Wire Bundle Diameter (inches)	1.125
Specifications	
Military Standard Part No.	MS3367-5
Temperature Rating	-40°F to 185°F
Flammability Rating	UL 94 V-2
Tooling	

ERG50, WT1-TB

100

100

1000

Regular



T&B Sold in UOM	Each
T&B Weight Per UOM	0.16 lbs. per 100
Application Support	
Overview	Available on Website
Material Selection Guide	Available on Website
Available Colors	Available on Website
Certifications	
RoHS Compliance	Yes

## For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com