Thomas&Betts





Standard T&B Catalog Number:

UPC Number: Status: Description: TY525MX 78621080510 Active

Cable Tie 50lb 7" Ultraviolet Resistant Black Nylon with Stainless Steel Locking Device Distributor Pack Features

	Oval low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulk- heads. Non-magnetic stainless steel locking device insures both maximum strength and the right tight- ness every time. Because there are no notches, Ty- Rap ties provide an infinite number of locking posi- tions while fastening the tie at the precise bundle di- ameter needed.
	The Turned-up Tail orients the tie for easy assem- bly, making the ties easier to pick up on a flat sur- face. The No-Slip Tail provides easy grip during tensioning. Ty-Rap ties feature a unique friction sur- face designed to reduce slippage during installation.
	Smooth, notchless body reduces stress concentra- tion points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, pre- venting sharp edges from damaging cables.
General	
Material	Nylon 6.6 Weather Resistant
Color	Black
Dimension Information	
Nominal Length (inches)	7
Length (inches)	7.31
Width (inches)	.185
Max. Wire Bundle Diameter (inches)	1.75
Specifications	
Military Standard Part No.	MS3367-1
Temperature Rating	-40°F to 185°F
Flamability Rating	UL 94 V-2
Tooling	
Application Tools	ERG50, WT1-TB
Packaging	
T&B Order Multiple	100
T&B Order Multiple T&B Inner Pack	100 100
•	



T&B Sold in UOM	Each
T&B Weight Per UOM	0.32 lbs. per 100
Application Support	
Overview	Available on Website
Material Selection Guide	Available on Website
Available Colors	Available on Website
Certifications	
RoHS Compliance	Yes

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com