



Juno[®]

Recessed and Trac Lighting

Save energy with Juno's stylish 4" CFL downlights

Juno has expanded the 4" CFL downlight offering to include new housings designed for non-insulated ceilings. Available in 13W, 18W, and 26W versions, they are up to 80% more energy efficient than equivalent incandescent lighting and last as much as 10-times longer. The small 4" apertures blend unobtrusively with even the most stylish decors and feature a diverse family of beautiful trims, including the 140 and 170 Series that are specially optimized for CFL illumination. These compact, single wall housings are designed for new construction applications (remodel housing also available for 26W version) and incorporate state-of-the-art electronic 120-277V ballasts that offer rapid starting and quiet, flicker-free operation.




JUNO LIGHTING GROUP[®]
an **AcuityBrands** company

Juno CFL downlights provide best-in-class performance

Juno's full line of 4" CFL downlights are designed and engineered in the USA to the highest standards and provide an energy-efficient, economical solution for task or general lighting in both residential and commercial applications. Juno's CFL housings are optimized for operation with pin-based CFL lamps and offer performance that is far superior to that of screw-in, retrofit lamps.

4" New Construction or Remodel

13 Watt CFL Housings



ICPL Fluorescent Housing
Air-Loc® CFL housing may be covered with insulation. Easy access ballast.

ICPL413E 120V HPF
Electronic Ballast

18½" L x 9¾" W x 7¼" H
Ceiling cutout: 4½"
One 13W Triple Tube (4-pin) CFL*



ICPL Fluorescent Remodel Housing
Air-Loc® CFL Remodel housing may be covered with insulation. Easy access ballast.

ICPL413RE 120V HPF
Electronic Ballast

12" L x 4¾" W x 6¼" H
Ceiling cutout: 4¾"
One 13W Triple Tube (4-pin) CFL*



PL Fluorescent Housing
Energy-efficient CFL housing. Requires 3" spacing from insulation.

PL413EU 120V thru 277V HPF
Electronic Ballast

11¾" L x 6¾" W x 6½" H
Ceiling cutout: 4½"
One 13W Triple Tube (4-pin) CFL*

18 Watt CFL Housings



ICPL Fluorescent Housing
Air-Loc® CFL housing may be covered with insulation. Easy access ballast.

ICPL418E 120V HPF
Electronic Ballast

18½" L x 9¾" W x 7¼" H
Ceiling cutout: 4½"
One 18W Triple Tube (4-pin) CFL*



ICPL Fluorescent Remodel Housing
Air-Loc® CFL Remodel housing may be covered with insulation.

ICPL418RE 120V HPF
Electronic Ballast

12" L x 4¾" W x 6¼" H
Ceiling cutout: 4¾"
One 18W Triple Tube (4-pin) CFL*



PL Fluorescent Housing
Energy-efficient CFL housing. Requires 3" spacing from insulation.

PL418EU 120V thru 277V HPF
Electronic Ballast

11¾" L x 6¾" W x 6½" H
Ceiling cutout: 4½"
One 18W Triple Tube (4-pin) CFL*

26 Watt CFL Housings



HPF/NPF ICPL Fluorescent Housing
Air-Loc® CFL housing may be covered with insulation. Easy access ballast.

ICPL426E 120V HPF Electronic Ballast
ICPL426EN 120V NPF Electronic Ballast
ICPL426EN-DB120 ICPL426EN with 120V NPF Dimmable Ballast – T24 compliant

18½" L x 9¾" W x 7¾" H
Ceiling cutout: 4½"
One 26W Triple Tube (4-pin) CFL*



PL Fluorescent Housing
Energy-efficient CFL housing. Requires 3" spacing from insulation.

PL426EU 120V thru 277V HPF Electronic Ballast

11¾" L x 6¾" W x 6½" H
Ceiling cutout: 4½"
One 26W Triple Tube (4-pin) CFL*



PL Fluorescent Remodel Housing
Energy-efficient CFL housing. Requires 3" spacing from insulation.

PL426RE 120V thru 277V HPF Electronic Ballast

11¾" L x 4¾" W x 7" H
Ceiling cutout: 4¾"
One 26W Triple Tube (4-pin) CFL*

4" 13/18/26 Watt CFL Trims

The trims shown here may be used with any 4" CFL housings.

Downlights



Pinhole with Integral Shield
13-WH
2" Aperture



Baffle
14W-WH White
14B-WH Black
14B-SC Black
14B-ABZ Black
14B-BL Black
3¾" Aperture



Cone
17CLI-WH Clear Low Iridescent Alzak®
17G-WH Gold Alzak®
17B-WH Black Alzak®
17PT-SC Pewter Alzak®
17W-WH Gloss White
17HZ-WH Haze
17WHZ-WH Wheat Haze
17WHZ-ABZ Wheat Haze
3¾" Aperture



Baffle
Optimized for CFL
140B-WH Black
140W-WH White
3¾" Aperture



Cone
Optimized for CFL
170CLI-WH Clear Low Iridescent Alzak®
170HZ-WH Haze
170WHZ-WH Wheat Haze
3¾" Aperture

Trim Ring Finishes

ABZ: Classic Aged Bronze
SC: Satin Chrome
WH: White
BL: Black

Decorative



Beveled Cylinder
4103FROST-WH
4103FROST-SC
3" Aperture



Beveled Cone
4104HZ-SC
4104WHZ-ABZ
3¾" Aperture



Glass Cylinder
4150MESH-SC
2¾" Aperture

Lensed



Drop Opal
11-WH



Frosted Lens with Clear Center
12W-WH
12W-SC
12W-ABZ



Beveled Frame, Frosted Dome Lens
4101-WH
4101-SC
4101-ABZ



Beveled Lens
4102-WH
4102-SC
4102-ABZ

Note: In Canada when insulation is present, Type IC fixtures must be used.
* Lamp not included.

©2016 Acuity Brands Lighting, Inc. The marks appearing in this catalog are trademarks of Acuity Brands Lighting, Inc. Products shown in this brochure may be covered by U.S. and international patents and patents pending. Specifications subject to change without notice.

Juno Lighting Group 1300 South Wolf Road | Des Plaines, IL 60018 | Ph: 847.827.9880 | www.junolightinggroup.com

Printed in the U.S.A. LIT-JUNO-4CFL 5/16



JUNO LIGHTING GROUP
an AcuityBrands company