



LEESON Electric Corporation

1051 Cheyenne Avenue

Grafton, WI 53024

E-Mail: sales@leeson.com • Web site: www.leeson.com



Item # 108014.00, DC NEMA SCR Rated 90 & 180 Volt Motors

List Price \$801.00

1/2HP.1750RPM.S56C.TEFC.90V.CONT.40C.1.0SF.RIGID C.DC NEMA.C4D17FK1J

[Specifications](#) · [Features / Advantages / Benefits](#) · [Application and Uses](#) · [Application](#)

Specifications

Motor Type	DF
Horsepower	1/2 hp
RPM	1750 RPM
Armature Voltage	90 V
Voltage	90 V
Current	5.00 A
Efficiency	78.3
Mount Type	Rigid C
Enclosure Type	TEFC
Frame Type	S56C
Insulation Type	F3
Temperature	40 °C
Shaft Diameter	5/8 in
C Dimension	12.82 in
Material	Rolled Steel
Weight	32 lb
Service Factor	1.0
Duty	CONT
Protector	Not
Shaft Length	1.875 in
Rotation	Reconn

Features / Advantages / Benefits

- Brush holder design provides easy access to brushes
- Large oversized brushes assure long brush life
- Removable bolt-on base
- Capable of dynamic braking
- High starting torque
- Permanently lubricated sealed bearings
- LEESON SCR controls available to power motors
- Higher HP and speed achievable using PWM type DC controls
- UL and CSA listed
- 10:1 constant torque operation

Application and Uses

- DC motors are typically used in applications requiring motor speed adjustment, constant torque through the speed range and reversing capabilities. Applications would include: pumps, conveyors, turntables, textile machinery, treadmills, reeling equipment, sports equipment and medical equipment

Application

General Purpose