

THIS IS NOT A CONSTRUCTION SITE, BUT A SAFER ENVIRONMENT THANKS TO PROPER TEMPORARY LIGHTING.



The new TL40PMT0 broadens McGill's extensive line of portable and temporary lighting, giving you a wide range of products with special features that save time and money while enhancing convenience and safety. Quality pays for itself in time savings, convenience, safety and longer reliable service.

The new TL40PMT0 offers:

- The Pulse Start Metal Halide fixture is complaint with the Energy Independence and Security Act of 2007 (EISA).
- Type "O" lamp and mogul socket complies with NEC 2008 Article 410.13(F)(5).
- Quick-attach durable 10" welded wire guard mounts directly to the body to protect from accidental impact.
- 3 foot cord with 5-15P molded plug on end.
- (2) 3/4" knock-outs for conduit access.

McGILL®

McGill HID Temporary Lighting Fixture



Shown with optional bottom trap

HID Temporary Lighting: Designed and Packaged for Quick Installation

More and more contractors are using temporary HID fixtures to light their work sites. Instead of modifying Low-Bay fixtures for this application, McGill's HID Temporary Lighting allows them to buy something faster and easier.

- 400W Pulse Start Metal Halide lamp provides over 6 footcandles of illumination at a 20 ft. mounting height
- McGill offers lighting layouts to conform with OSHA requirements for light output
- UL and cUL Listed, Suitable for Damp Locations
- **Type "O" lamp and mogul socket complies with NEC 2008 Article 410.13(F)(5) and ANSI C78.387**
- Quick-attach durable 10" welded wire guard mounts directly to the body to protect lamp and lampholder from accidental impact
- Fixture is factory wired at 120V, but can be rewired internally for other voltage settings
- 3 foot cord with 5-15P molded plug on end
- Compact size for easy handling
- Low-profile fixture design keeps it up and out of the way of activity below
- High light output and long lamp life
- Open-air ballast for cooler operation
- Hook with locking feature
- (2) 3/4" knock-outs for conduit access
- Single durable package design makes it easier for distributors to stock and more organized for contractors on the job site
- Quick and easy to assemble
- Optional bottom trap available

Selection Chart


	Catalog Number
400 watt fixture	TL40PMT0

Accessories and Replacement Parts

	Catalog Number
Bottom trap	TLTRAPW
Lamp guard	TLGUARDW
Lamp - pulse start metal halide - Type "O" (clear)	GMP400BUPS

Standard Materials

- Enclosure: Heavy-duty steel with powder-coated finish
- Lamp: 400 Watt Pulse Start Metal Halide: O-Type, BT37 Clear, EX39 (Exclusionary Mogul Base)
- Multi-Tap ballast: 120V, 208V, 240V, 277V: Factory wired at 120V
- Power cord: 3 FT, 18/3 SJTW, 120V, 15Amp cord complete with NEMA 5-15 molded plug
- Lamp guard: 11 ga. white painted steel
- Mounting hook: 11 ga. steel



Spring-lock hook allows contractors to mount the unit in seconds, without the need for tools.

DIMENSIONS inches

