







CADDY SLICK NUT – SLICK375



- Provides fast universal attachment of threaded rod and hardware to standard strut profiles



| | |
|-----------------------------|---------------------------|
| Part Number | SLICK375 |
| Material | Polyamide Spring Steel |
| Finish | CADDY ARMOUR |
| Hole Size (HS) | 3/8" |
| Hole Type | Threaded |
| Height (H) | 11/16" |
| Torque (TQ) | 10 ft lb |
| Static Load 1 (F1) | 600 lb |
| Static Load 2 (F2) | 100 lb |
| Static Load 3 (F3) | 250 lb |
| Standard Packaging Quantity | 100 pc |
| UPC | 78285641672 |

Indicated loads are independent of the threaded stud or rod.

Indicated loads are applicable on 14 GA and 12 GA (2 mm and 2.5 mm) strut channels only.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

