



# PAR30/PAR20 LED

## 12.5PAR30L/F35 4000 DIM SO

Philips PAR30 and PAR20 LED Single Optic Lamps provide superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

### Product data

General Information	
Cap-Base	E26 [ Single Contact Medium Screw]
Bulb Shape	PAR30L [ PAR 3.75 inch/95mm Long]
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X
Technical Type	12.7-75W

Light Technical	
Color Code	841 [ CCT of 4100K (841)]
Beam Angle (Nom)	35 °
Initial lumen (Nom)	950 lm
Luminous Flux (Rated) (Nom)	950 lm
Luminous Intensity (Nom)	2600 cd
Color Designation	Cool White (CW)
Rated Beam Angle	35 °
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	75 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	12.7 W

Lamp Current (Nom)	125 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.85
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	89 °C

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy star mark	Energy star
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	Not applicable

Product Data	
Order product name	120V PAR30L 12.7W 35D 4000K 900 D SO
EAN/UPC - Product	046677454715
Order code	454710
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6


## PAR30/PAR20 LED

Material Nr. (12NC)	929001132804
Net Weight (Piece)	0.001 kg

### Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.
- CAUTION: Risk of electric shock— do not use where directly exposed to water
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005.

### Dimensional drawing



PAR30L CL 120V 12.5W-75W 35D 4000K E26 D

Product	D	C
120V PAR30L 12.7W 35D 4000K 900 D SO	92 mm	116 mm

### Photometric data

