



Core & Coil (71A) HPS ~LT~ 200W

CORE & COIL HID 71A7907600B

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	S62
Lamp Type	70W HPS
Number Of Lamps	1 piece/unit
Circuit Type	R-NPF
Ballast Type	Magnetic HID
Base Model	71A7907B_NPF
Core Size	2 5/8 x 2 3/16
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	INTEGRAL
Ignitor Temperature Rating	125°C
Capacitor Value	NA
Capacitor Catalog Number	NA
Capacitor Requirements	NA
Capacitor Temperature Rating	NA
Automatic Restart	No
Operating and Electrical	
Input Voltage	120 V
Input Frequency	60 Hz

Input Current (Open Circuit)	0 A
Input Current (Starting)	2.1 A
Input Current (Short Circuit)	1.9-2.9 A
Secondary Short Circuit Current	1.9-2.9 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.43
Open Circuit Voltage	120 V
Input Current (Nom)	1.6 A A
Input Power (Nom)	86 W
Rated Lamp Power	70W W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	2'
Recommended Fuse Value	8 A

Core & Coil (71A) HPS ~LT~ 200W


Approval and Application

Open Circuit Voltage Test (Volts)	114-126 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A

Product Data

Order product name	CORE & COIL HID 71A7907600B
EAN/UPC - Product	781087790779
Order code	176859
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	913700501771
Net Weight (Piece)	0.894 kg

Dimensional drawing



HPS BAL 70W S62 120V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A7907600B	2.90 in	1.3 in	2.6 in	2.2 in	2.2 in	1.8 in

