


RELAY CONFIGURATION


CODE (1)	INPUT VOLTAGE	VOLTAGE	HORSEPOWER RATING	AMPS	CONTACTS
42	AC 50/60 HZ	120VAC	1/6	10	SILVER
		240VAC	1/3		CADMIUM
D42	DC	30VDC	-		OXIDE

VOLTAGE	50/60HZ CODE (2)
6	V35
12	V36
24	V14
120	V20
240	V24


VOLTAGE	DC CODE (2)
12	V51
24	V53
110	V80




TOP VIEW




BACK VIEW



FRONT VIEW



RIGHT VIEW



BOTTOM VIEW

CONTACT ARRANGEMENT FOR ALL RELAYS: 2PDT

Catalog Number: 8501-R5(1)(2)
 Ratings: SEE CHART
 UL File/CCN: E78351-NLDX2
 CSA File/Class: LR35144-3211-04
 Meets Standards: -
 Weight: -
 Wire Size: -
 Terminal torque: -
 Mounting Hwd.: -

DUAL DIMENSIONS: INCHES
 MILLIMETERS

GENERAL PURPOSE MINIATURE
 PLUG-IN RELAY (14 BLADE)
 8501-R5(1)(2)



DWG# E0704301-01
 NO.