

Product availability : Stock - Normally stocked in distribution facility



### Main

Range of product	Square D
Product or component type	Energy Efficient Transformer
Device application	Low voltage electrical distribution
Number of tap-offs	2-2.5 % FCAN 4-2.5 % FCBN

### Complementary

Primary voltage	480 V delta
Rated operational power in VA	75 kVA
Type of cooling	Natural convection
Secondary voltage	208Y/120 V
Network frequency	60 Hz
Phase	3 phases
AWG gauge	AWG 6...350 kcmil AWG 14...AWG 2/0
Temperature rise	150 °C 220 °C insulated
Material	Aluminium
Mounting support	Floor Ceiling, with specific accessories Wall, with specific accessories
Depth	577.85 mm
Width	763.6 mm
Height	42 in (1066.8 mm)
Product weight	281.23 kg
Efficiency	98.69 %

### Environment

Standards	NEMA ST-20
-----------	------------

UL 1561

Degree of protection	UL type 1 UL type 3R, with accessory
----------------------	---

### Ordering and shipping details

Category	16250 - 3PH EX/2016 15-150KVA LVGP XFMR
Discount Schedule	PE2X
GTIN	00785901405719
Nbr. of units in pkg.	1
Package weight(Lbs)	647
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1536 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations