

GS2EU3N

TeSys GS - switch-disconnector-fuse - 3 P - UL -
30 A- fuse size J

Product availability : Stock - Normally stocked in distribution facility

Price* : 260.00 USD



Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2EU
Product or component type	Switch-disconnector-fuse
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I _{th}] conventional free air thermal current	30 A at 104 °F (40 °C)
[I _e] rated operational current	30 A
Fuse type	UL
Fuse size	J
Network type	AC DC
Network frequency	50/60 Hz

Complementary

Type of operating handle	External frontal
Mounting support	Plate Rail
[U _i] rated insulation voltage	750 V
[U _{imp}] rated impulse withstand voltage	8 kV
Rated operational power in W	15 kW at 400 V 25 kW at 690 V 18.5 kW at 500 V
Short-circuit withstand	17.6 kA
Mechanical durability	10000 cycles

Connections - terminals	Power circuit : lugs-ring terminals cable 2...13 mm ²
Tightening torque	Power circuit : 6.6 N.m

Environment

Standards	CSA C22.2 No 4 UL98
IP degree of protection	IP20 with terminal cover conforming to IEC 60529
Ambient air temperature for operation	-4...158 °F (-20...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Fire resistance	1760 °F (960 °C) body
Height	5.35 in (136 mm)
Width	5.88 in (149.3 mm)
Depth	4.84 in (123 mm)

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901149460
Nbr. of units in pkg.	1
Package weight(Lbs)	3.79
Returnability	Y
Country of origin	TN

Offer Sustainability

Sustainable offer status	Not Green Premium product
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold