



**TERMINAL LUG DATA †**

AMPERES	MAX WIRE	MIN WIRE	TYPE
100	#1/D AWG	#14 AWG	CU
100	#1/D AWG	#12 AWG	AL

DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS																							
				240VAC						480VAC						250 VDC		600 VDC									
				STD			MAX			STD			MAX			STD		MAX									
				1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	STD	MAX	STD	MAX					
H363DSWA	600VAC,250VDC	100	A	-	-	-	-	-	-	10*	-	25	30*	-	60	-	-	30	-	-	20*	-	-	-			
HU383DSWA	800VAC,250VDC	100	B	-	-	-	-	-	-	-	-	-	40*	-	75	-	-	-	40*	-	75	-	-	20*	-	-	-

NOTES:  
FINISH - TYPE 304 STAINLESS STEEL  
UL LISTED - E2875

SHORT CIRCUIT CURRENT RATINGS:  
10,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS H FUSES.  
200,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS J OR R FUSES.

\* USE OUTER SWITCHING POLES.  
† LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

**HEAVY DUTY SAFETY SWITCHES**  
VISIBLE BLADES  
100 AMPERE-SERIES F7  
ENCLOSURE-NEMA TYPE 4, 4X AND 5 STAINLESS STEEL



DMC# 3183  
NO.