


| ſ | CODE | AUX CONTACTS | | TYPE OF CONNECTION |
|---|------|--------------|----|--------------------|
| L | (1) | NO | NC | |
| | 40 | 4 | - | |
| ſ | 31 | 3 | 1 | SCREW CLAMP |
| Γ | 22 | 2 | 2 | |
| | 13 | 1 | 3 | |
| | 04 | - | 4 | |

Block of 4 contacts cannot be used with LP4-K or LP5-K contactors.

| TYPE OF CABLE | WIRE SIZE |
|----------------------------------|-----------|
| STANDARD CABLE WITHOUT CABLE END | AWG 16-10 |
| STANDARD CABLE WITH CABLE END | AWG 18-10 |
| SOLID CABLE | AWG 22-12 |







Catalog Number: LA1 KN(1)
Ratings: —
UL File/Guide: — CSA File/Guide: -Meets Standards: -

Weight: SEE CHART Wire Size:

Terminal torque: 7 LB-IN
Mounting Hwd.: CLIP-ON FRONT MOUNTING

"THE SQUARE D COMPANY HAS PROPRIETARY RIGHTS TO THE INFORMATION CONTAINED HEREON. THIS INFORMATION REMAINS THE PROPERTY OF SQUARE D COMPANY AND MAY BE USED ONLY IN CONFORMANCE WITH INSTRUCTIONS ISSUED BY SQUARE D COMPANY. USER SHOULD VERIFY DRAWINGS ARE TO THE LATEST/CURRENT REVISION PRIOR TO INCORPORATING IN A DESIGN FILE."



IEC CONTACT BLOCK (K-LINE) LA1 KN(1)



NOVEMBER 2000

E0210801