

CERTIFICATE OF COMPLIANCE

Certificate Number 20161003- E164353
Report Reference E39281-19981027
Issue Date 2016-OCTOBER-03

Issued to: Schneider Electric Industries S A, DBA Telemecanique
8001 Knightdale Blvd, Knightdale NC 27545

**This is to certify that
representative samples of**

AUXILIARY DEVICES
See Addendum page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

Industrial Control Equipment, UL 508
See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20161003- E164353
Report Reference E39281-19981027
Issue Date 2016-OCTOBER-03

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL - Push button and pilot light assemblies (22 mm line) Cat. No. XB4 - B or XB5 A followed by A, C, D, G, H, J, K, L, P, R, S, T, V, W or X, followed by two, three, four, five or six numbers and / or letter suffixes.

Contact blocks, Cat. No. ZBE, followed by 0, 1 or 2, followed by two digit number, may be followed by 6 or 6P, may be followed by 3, 5 or 9, may be followed by J. ZEN L followed by 1111 or 1121.

Pilot light blocks, Cat. No. ZBV 6 followed by one digit, may be followed by 3, 5 or 9, Cat. No. ZBV or ZBV 18 followed by B, J, G, M, or BG, followed by one digit, may be followed by 3, 5, 9 or S. Cat. No. ZAL V or ZAL V18 followed by B, J, G, M, or BG followed by one digit.

Test output unit, Cat. No. ZB.-.V156,ZB.-.VB.156 and ZBZ-.156.

Contact Subunit, Cat. No. ZB4 - BZ or ZB5 - AZ followed by a three digit or four digit number, Cat. No. ZD4-PA or ZD5-PA followed by a three digit number.

Pilot light subunit, Cat. No. ZB4 - BV or ZB5 - AV followed by one, two, three or four numbers and / or letter suffixes.

LED pilot light transient voltage suppressors subunit, Cat. No. ZBZ VG or ZBZ VM.

Illuminated push button subunit, Cat. No. ZB4 - BW0 or ZB5 - AW0 followed by two, three, four or five numbers and / or letter suffixes.

Operators, Cat. No. ZB4 - B, ZB5 - A or ZB5 - C, followed by A, B, C, D, F, G, H, J, K, L, P, R, S, T or X, followed by 1, 2, 3, 4 5, 6, 7, 8 or 9, followed by one, two, three or four numbers, may be followed by M and/or 7. Cat. No. ZD4-PA or ZD5-PA followed by a two digit number.

Pilot light heads, Cat. No. ZB4 - BV0, ZB5 - AV0 or ZB5 - CV0 followed by one or two numbers may be followed by S.

Illuminated operators, Cat. No. ZB4 - B, ZB5 - A or ZB5 - C followed by W, A, H, P, K or L followed by one, two, three, four or five numbers may be followed by 3, may be followed by S, may be followed by 7.

Joystick controllers, Cat. No. XD4-PA or XD5-PA followed by a two digit number may be followed by a letter.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

