

Molded Case Circuit Breakers

QJ 225A Frame

Type QJ2^②

Continuous Current Rating @ 40°C	2-Pole	3-Pole
	240V AC	240V AC
	Catalogue Number	Catalogue Number
60	QJ22B060	QJ23B060
70	QJ22B070	QJ23B070
80	QJ22B080	QJ23B080
90	QJ22B090	QJ23B090
100	QJ22B100	QJ23B100
110	QJ22B110	QJ23B110
125	QJ22B125	QJ23B125
150	QJ22B150	QJ23B150
175	QJ22B175	QJ23B175
200	QJ22B200	QJ23B200
225	QJ22B225	QJ23B225

Type QJH2^②

60	QJH22B060	QJH23B060
70	QJH22B070	QJH23B070
80	QJH22B080	QJH23B080
90	QJH22B090	QJH23B090
100	QJH22B100	QJH23B100
110	QJH22B110	QJH23B110
125	QJH22B125	QJH23B125
150	QJH22B150	QJH23B150
175	QJH22B175	QJH23B175
200	QJH22B200	QJH23B200
225	QJH22B225	QJH23B225

Type QJ2H^②

60	QJ22B060H	QJ23B060H
70	QJ22B070H	QJ23B070H
80	QJ22B080H	QJ23B080H
90	QJ22B090H	QJ23B090H
100	QJ22B100H	QJ23B100H
110	QJ22B110H	QJ23B110H
125	QJ22B125H	QJ23B125H
150	QJ22B150H	QJ23B150H
175	QJ22B175H	QJ23B175H
200	QJ22B200H	QJ23B200H
225	QJ22B225H	QJ23B225H

Type HQJ2^④

100	—	HQJ23B100H
110	—	HQJ23B110H
125	—	HQJ23B125H
150	—	HQJ23B150H
175	—	HQJ23B175H
200	—	HQJ23B200H
225	—	HQJ23B225H

QJ2

Internal Accessories (**Factory installed only**) 3-pole only^③.

Add suffix to catalogue number.

Control Voltage		Shunt Trip Suffix	Auxiliary Switches		Shunt Trip and 1A and 1B Auxiliary Switch Suffix
AC	DC		1A and 1B Suffix	2A and 2B Suffix	
120/240	—	00S01	A01	A02	01S01
—	24	00S07	A01	A02	01S07
—	25	00S11	A01	A02	01S11

① See Note: A page 5-64.
 Note: QJ Breakers are UL Listed for reverse feed applications.
 ② HACR rated.

③ Internal accessories are **not available** on 2-pole QJ breakers.

④ HQJ2 is 65kAIC @ 240VAC and 100kAIC @ 208VAC.

Selection/Dimensions

Ordering Information

Load side TA1Q300 lugs are mounted and included when circuit breaker is ordered. For line and load lugs (TA1Q300) installed at no additional charge, add suffix "L" to catalogue number.

50°C Calibration - See page 5-67.

400HZ. - See page 5-67.

Shipping Weights

QJ2, QJH2, QJ2H, HQJ2H		
Number of Poles	Number per Carton	Shipping Weight (lbs.)
2	10	30
3	10	41

Lugs For 75°C Wire^①

Catalogue Number	Lug Body	Lug Wire Range
TA1Q300	Al	(1) #6–300 kcmil Cu (1) #4–300 kcmil Al
TC1Q250	Cu	(1) #6–250 kcmil Cu

UL 489 Interrupting Ratings

Breaker Type	AIR @ 240V AC
QJ2	10,000
QJH2	22,000
QJ2H	42,000
HQJ2H	65,000

