Product data sheet Characteristics

2510KG2C

Manual Switch - NEMA 1 - 3P - Toggle Operated - Red Indicator - 600VAC

Product availability: Stock - Normally stocked in distribution facility



Price*: 223.20 USD



Main

Product or component type	Single Unit Manual Switch	——broduc
Range of product	K	lese

Complementary

	<u>0</u>
30 A	ō
0.5" and 0.75" knock-outs (top and bottom)	
2 hp at 115 V AC	ins
1 hp at 90 V DC	igi
2 hp at 115 V DC	
	0
	for
	Se de la company
10 hp at 575 V AC	
600 V AC	9
230 V DC	and is not to be used for determining suitability
3P	
Toggle	for
3 phases	substitute for
Red indicator 440600 V	a
Non reversing	is not intended as
Screw clamp terminals	
AWG 14AWG 10 (copper)	
4.25 in	. <u></u>
2.44 in	ocumentation
2.75 in	- English
	0.5" and 0.75" knock-outs (top and bottom) 2 hp at 115 V AC 1 hp at 90 V DC 2 hp at 115 V DC 1.5 hp at 230 V DC 7.5 hp at 230 V AC 10 hp at 460 V AC 10 hp at 575 V AC 600 V AC 230 V DC 3P Toggle 3 phases Red indicator 440600 V Non reversing Screw clamp terminals AWG 14AWG 10 (copper) 4.25 in 2.44 in

Environment

Decided at a configuration	OOA DOE400 -1 0044 0F
Product certifications	CSA LR25490 class 3211 05

NEMA degree of protection	NEMA 1 plastic standard size	

Ordering and shipping details

Category	21102 - 2510,2511,2512 K		
Discount Schedule	CP1		
GTIN	00785901554523		
Nbr. of units in pkg.	3		
Package weight(Lbs)	0.88		
Returnability	Υ		
Country of origin	MX		

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will be compliant on 3Q2014	
	Will be compliant on 3Q2014	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	

Contractual warranty

-		
Warranty period	18 months	