Product data sheet Characteristics

RPZF1

socket RPZ - mixed contact - 16 A - 250 V - screw clamp

Product availability: Stock - Normally stocked in distribution facility

Price*: 4.30 USD



Main

Range of product	Zelio Relay
Product or component type	Socket
Contact terminal arrangement	Mixed
Product compatibility	Plug-in relay RPM (1 C/O)
Device short name	RPZ

Complementary

[Ith] conventional free air thermal current	15 A	
System Voltage	250 V	
Tightening torque	<= 8.85 lbf.in (1 N.m) (M3.5 screw(s)) <= 7.08 lbf.in (0.8 N.m) (M3 screw(s))	
Fixing mode	By screw mounting on panel Clip-on mounting on 35 mm symmetrical DIN rail	
Product weight	0.07 lb(US) (0.031 kg)	

Environment

Connections - terminals	Contact terminal - screw clamp terminals, 2 wires solid cable without cable end 0.54 mm² / AWG 20AWG 12
	Contact terminal - screw clamp terminals, 1 wire solid cable without cable end 0.54 mm² / AWG 20AWG 12
	Contact terminal - screw clamp terminals, 2 wires flexible cable with cable end 0.52.5 mm² / AWG 20AWG 14
	Contact terminal - screw clamp terminals, 1 wire flexible cable with cable end 0.52.5 mm² / AWG 20AWG 14
	Coil terminal - screw clamp terminals, 2 wires solid cable without cable end 0.52.5 mm² / AWG 20AWG 14
	Coil terminal - screw clamp terminals, 1 wire solid cable without cable end 0.52.5 mm² / AWG 20AWG 14

	Coil terminal - screw clamp terminals, 2 wires flexible cable with cable end 0.51.5 mm² / AWG 20AWG 16 Coil terminal - screw clamp terminals, 1 wire flexible cable with cable end 0.51.5 mm² / AWG 20AWG 16
Standards	IEC 61984 UL 508 CSA C22.2 No 14
Product certifications	CE CSA RoHS UL REACH EAC China RoHS
Ambient air temperature for storage	-40185 °F (-4085 °C)
Ambient air temperature for operation	-40131 °F (-4055 °C)
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

Ordering and shipping details

Category	21128 - ZELIO ICE CUBE RELAY ACCESSORIES
Discount Schedule	CP2
GTIN	00785901573265
Nbr. of units in pkg.	10
Package weight(Lbs)	8.999999999997E-2
Returnability	Υ
Country of origin	CN

Contractual warranty

<u></u>	
Warranty period	18 months