

# RXZE2M114

socket RXZ - mixed contact -10A - < 250V - screw clamp -for relay RXM2.., RXM4..

Product availability : Stock - Normally stocked in distribution facility

Price\* : 5.00 USD



## Main

Range of product	Zelio Relay
Product or component type	Socket
Contact terminal arrangement	Mixed
Product compatibility	Plug-in relay RXM (2 C/O) Plug-in relay RXM (4 C/O)
Shape of pin	Flat
Device short name	RXZ
Sale per indivisible quantity	10

## Complementary

[I <sub>th</sub> ] conventional free air thermal current	10 A
System Voltage	< 250 V
Tightening torque	<= 8.85 lbf.in (1 N.m) (M3 screw(s))
Fixing mode	By screw panel Clip-on 35 mm symmetrical DIN rail
Marking	CE
Width	1.18 in (30 mm)
Product weight	0.11 lb(US) (0.048 kg)

## Environment

Connections - terminals	Screw clamp terminals, flexible cable with cable end 1 x 0.25...1 x 1 mm <sup>2</sup> / AWG 22...AWG 17 Screw clamp terminals, flexible cable with cable end 2 x 0.25...2 x 1 mm <sup>2</sup> / AWG 22...AWG 17 Screw clamp terminals, solid cable without cable end 1 x 0.5...1 x 1.5 mm <sup>2</sup> / AWG 20...AWG 16 Screw clamp terminals, solid cable without cable end 2 x 0.5...2 x 1.5 mm <sup>2</sup> / AWG 20...AWG 16
Standards	IEC 61984
Product certifications	Lloyd's CSA

## UL

Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Ambient air temperature for operation	-40...131 °F (-40...55 °C)
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

## Ordering and shipping details

Category	21128 - ZELIO ICE CUBE RELAY ACCESSORIES
Discount Schedule	CP2
GTIN	00785901758044
Nbr. of units in pkg.	10
Package weight(Lbs)	0.12
Returnability	Y
Country of origin	CN

## Contractual warranty

Warranty period	18 months
-----------------	-----------