

Product data sheet

Characteristics

2510FG2P

MANUAL STARTER 277VAC

Product availability : Stock - Normally stocked in distribution facility



Price* : 144.40 USD



Main

Product or component type	Single Unit Manual Starter
Range of product	F
Thermal overload type	Melting alloy

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Ordering and shipping details

Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901553960
Nbr. of units in pkg.	1
Package weight(Lbs)	0.8200000000000006
Returnability	Y
Country of origin	MX

Contractual warranty

Warranty period	18 months
-----------------	-----------

Complementary

Line Rated Current	16 A
Cable entry	0.5" and 0.75" knock-outs (top and bottom)

Motor power hp	1 hp 230 V AC 0.75 hp 115 V DC 0.75 hp 230 V DC 1 hp 115 V AC 1 hp 277 V AC
System Voltage	277 V AC 230 V DC
Poles description	2P
Control type	Toggle switch
Phase	1 phase
Local signalling	Red indicator
Reset	Manual
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals

Environment

Product certifications	CE CSA UL listed
NEMA degree of protection	NEMA 1 plastic standard size