



TERMINAL LUG DATA ‡			
AMPERES	MAX WIRE	MIN WIRE	TYPE
30	#6 AWG	#12 AWG	AL
30	#6 AWG	#14 AWG	CU

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS												250 VDC		600 VDC							
				240VAC			480VAC			600VAC															
				STD		MAX	STD		MAX	STD		MAX													
				1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	STD	MAX	STD	MAX						
H361SS	600VAC,600VDC	30	A	-	-	-	-	-	3*	-	5 ♦	7.5*	-	15 ♦	-	-	7.5	-	-	20	5*	-	10*	15*	
HU361SS	600VAC,600VDC	30	B	-	-	-	5*	-	10 ♦	-	-	7.5*	-	20 ♦	-	-	-	-	10*	-	30	-	5*	-	15*

NOTES:
 FINISH - TYPE 316 STAINLESS STEEL
 UL LISTED - E2875
 CSA - FILE PER REFERENCE 158337 REPORT 1100916 (LL 89067-45)
 ALL NEUTRALS - INSULATED
 SHORT CIRCUIT CURRENT RATINGS:
 10,000 RMS SYMMETRICAL AMPERES WHEN USED IN CONJUNCTION WITH CLASS H OR K FUSES
 200,000 RMS SYMMETRICAL AMPERES WHEN USED IN CONJUNCTION WITH CLASS R, J OR T FUSES
 *USE BOTH OUTER SWITCHING POLES
 ♦FOR CORNER GROUNDED DELTA INSTALL NEUTRAL AND USE OUTER SWITCHING POLES FOR UNGROUNDED CONDUCTORS.
 ‡LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADES
 30 & 60 AMPERE-SERIES F6
 ENCLOSURE-NEMA TYPE 4, 4X AND 5 STAINLESS STEEL

SQUARE D
 by Schneider Electric
 DWG# 3331
 NO.