



TERMINAL LUG DATA ‡			
AMPERES	MAX WIRE	MIN WIRE	TYPE
200	250 KCMIL	#6 AWG	CU/AL

DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS													
			240VAC				480VAC				600VAC				250 VDC	600 VDC
			STD		MAX		STD		MAX		STD		MAX		STD	STD
			2Ø	3Ø	2Ø	3Ø	2Ø	3Ø	2Ø	3Ø	2Ø	3Ø	2Ø	3Ø		
H464DS	600VAC;600VDC	A	30	25	50	60	50	50	—	125	50	60	—	150	40	50
H664DS	600VAC;600VDC	C	15▲	25	—	60	25▲	50	50▲	125	30▲	60	50▲	150	40	50
HU464DS	600VAC;600VDC	B	—	—	50	60	—	—	50	125	—	—	50	150	40<	50<
HU664DS	600VAC;600VDC	D	—	—	15▲	60	—	—	50▲	125	—	—	50▲	150	40<	50<

NOTES:  
 FINISH — TYPE 304 STAINLESS STEEL  
 UL LISTED — E2875  
 SHORT CIRCUIT CURRENT RATINGS:  
 10,000 AMPERES WITH CLASS H OR K FUSES.  
 200,000 AMPERES WITH CLASS R OR J FUSES.  
 ON 600V SWITCHES, 100,000 AMPERES MAX ON CORNER GROUNDED DELTA WHEN PROTECTED BY CLASS J OR R FUSES, 200 AMPERE MAX.  
 NOT SUITABLE FOR USE AS SERVICE EQUIPMENT  
 ‡ LUGS SUITABLE FOR 75°C CONDUCTORS.  
 ▲ 1Ø RATING  
 < MAX RATING

HEAVY DUTY SAFETY SWITCHES  
 VISIBLE BLADE TYPE  
 200 AMPERE — SERIES F6  
 ENCLOSURE — NEMA 4, 4X AND 5 STAINLESS STEEL



DWG# 3231  
NO.