

Product availability : Stock - Normally stocked in distribution facility



Price\* : 2600.00 USD



### Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Line Rated Current	125 A
Trip unit technology	Thermal-magnetic
Breaking capacity code	D

### Complementary

Poles description	3P
Breaking capacity	20 kA 250 V DC 18 kA 480 V AC 14 kA 600 V AC 25 kA 240 V AC
System Voltage	250 V DC 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Mounting mode	Unit mount
Electrical connection	Lugs line Lugs load
AWG gauge	AWG 14...AWG 3/0 (aluminium/copper)
Magnetic hold current	900 A
Magnetic tripping current	1700 A

### Environment

Product certifications	CE CSA IEC UL listed
------------------------	-------------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Ordering and shipping details

Category	01110 - HD,JD UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901955849
Nbr. of units in pkg.	1
Package weight(Lbs)	4.1200000000000001
Returnability	Y
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------