

Product availability : Stock - Normally stocked in distribution facility



Price* : 3779.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Line Rated Current	200 A
Number of poles	3
Poles description	3P
Trip unit technology	Thermal-magnetic
Breaking capacity code	G

Complementary

Breaking capacity	35 kA 480 V AC 18 kA 600 V AC 20 kA 500 V DC 65 kA 240 V AC 20 kA 250 V DC
System Voltage	600 V AC 250 V DC 500 V DC
[Ics] rated service short-circuit breaking capacity	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 3/0...350 kcmil (aluminium/copper)
Magnetic hold current	1000 A
Magnetic tripping current	2000 A

Environment

Product certifications	CCC CE CSA
------------------------	------------------

IEC
UL listed

Ordering and shipping details

Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901683216
Nbr. of units in pkg.	1
Package weight(Lbs)	4.8600000000000003
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------