



Disconnects T&B Catalog Number:

UPC Number: Status: Description:


General

RB2573 78621085680 Active

Nylon Fully Insulated Female Disconnect, Length 1.01 Inches, Width .38 Inches, Maximum Insulation .185, Tab Size .250x.032, Wire Range #16-#14 AWG, Color Blue, Brass, Tin Plated, 1,000 Pack Features

> Unique construction of the female disconnect offers long-term dependability. Brazed seam serrated barrel provides maximum tensile strength.

General	
Disconnect Type	Female - 250 Series
Insulation Type	Fully Insulated Nylon
Terminal Series	RB
Material	Brass
Finish	Electro -Tin Plated
Color	Blue
Wire Range	16-14
Tab Size	.250 x .032
Dimension Information	
Maximum Insulation (inches)	.185
Stock Thickness	.03
A (inches)	.97
B (inches)	.38
Specifications	
Temperature Rating	105°C
Voltage Rating	600V
Flammability Rating	UL 94 V-2
Tooling	
Tool Charts	Available on Website
Application Tools	WT145C, WT2000, WT112M, ERG4001, ERG4003
Recommended Tool	ERG4001
Packaging	
T&B Order Multiple	1000
T&B Inner Pack	1000
Package in Units	10000
Package Type	Bulk
T&B Sold in UOM	Each
T&B Weight Per UOM	3.75 lbs. per 1000
Alternate Package Qty	14RB2577
Application Support	
Overview	Available on Website
Wire Guide Tables	Available on Website



Certifications

(U) File Nbr:

E66716

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Ð

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com