

#### 68-P - Round Nonmetallic Floor Box

The 68-P floor box provides flush service for power, communications and data. The nonmetallic floor box is used in concrete floors and is suitable **for carpet, tile or wood applications**.

- High-strength rigid PVC construction, non-corrosive
- Easy installation with no leveling required just cut the box level with the concrete after the pour
- Compatible with standard-schedule PVC conduit (1 in., 3/4 in. and 1/2 in. reducers included)
- · Pre-packaged with concrete cap and six hub plugs



Cat.	Dimensions (in.)		After Pour	Maximum Capacity	Standard Conduit	Covers and	Wiring	Std.	
	A	В	С	Adj. (in.)	(cu. in.)	Tapping (in.)	Carpet Plates	Device	Ctn.
68-P	5-5/32	6	6-3/8	None	100	(4) 3/4 (2) 1	P60 P68 Series	Single Duplex or data/voice	8

Minimum pour 3 inches

Cubic in. capacity is 17 cubic inches per inch of box height Note: must use 68-PAR to attach cover plates to 68-P floor box

### **Adjusting Ring for 68-P Floor Box**



Cat. No.	Description	Std. Ctn.
68-PAR	Nonmetallic Adjusting Ring	8

Nonmetallic adjusting ring includes pigtail and clips Required to mount P60 and P68 Series covers to 68P floor box (not needed for dual-voltage kits)

#### **Metallic Tile Trims for 68-P Floor Box**



 Tile trim rings are available in brass or aluminum for flush installation of metallic plates in linoleum, wood or carpeted floors. Must be used to mount P60 Series plates (Not required for P68 covers, P60-CACP, P60-CACP-AL or P60-3/4-2-CACP)



Cat. No.	Description	Std. Ctn.
68P-FL	Metallic Tile Trims	8

Required to attach P60 cover plates to 68-P floor box





#### **MopTite™ Metallic Carpet Plates for 68-P Series**

- · Polished brass finish
- Furnished complete with 8-32 x 1 in. brass screws
- For brushed aluminum, add AL after catalogue number



P-60-CACP



communications carpet plate. 4-3/4 in. O.D. Mounting holes 3-3/8 in. dia.

P-60-3/4-2-CACP P-One-piece solid-brass



P-60-CACP-GFCI



P-60-CP




Cat. No.	Description	Finish	Std. Ctn.
P-60-CP•	Carpet Plate, 5-11/16 in. diameter	Brass	
P-60-CP-AL•	Carpet Plate	Aluminum	
P-60-CACP	One Diese Counct Diete	Brass	
P-60-CACP-AL	One-Piece Carpet Plate	Aluminum	4
P-60-3/4-2-CACP	One Diese Counch Dieke with 2/4 in . O in Divers	Brass	4
P-60-3/4-2-CACP-AL	One-Piece Carpet Plate with 3/4 in 2 in. Plugs	Aluminum	
P-60-CACP-GFCI•	One Diseas Council Disks for CECL Devises	Brass	
P60-CACP-GFI-AL•	One-Piece Carpet Plate for GFCI Devices	Aluminum	

Requires 68P-FL or 68P-FL-AL to attach covers to 68-P Floor Box
New MopTite™ Covers exceed UL watertight requirements for 514A, 514C

### **MopTite<sup>™</sup> Nonmetallic Carpet Plates for 68-P Series**

Nonmetallic, single receptacle plate (SRC) with matching carpet plate and cover. 6 in. O.D.



1-13/32 in. Dla. Opening Nonmetallic floor service cover (FSC) with 1 in. screw plug accommodates most above-floor service fittings with matching carpet plate. 6 in. O.D.



Nonmetallic, duplex/voice data receptacle plates (DRC) with matching carpet plate and cover. 6 in. 0.D.







Cat. No.	Description	Colour	Std. Ctn.
P-68-SRC-GRY		Grey	
P-68-SRC-BRN	For Cinale Becombook	Brown	
P-68-SRC-BGE	For Single Receptacle	Beige	4
P-68-SRC-BLK		Black	4
P-68-FSC-GRY	With 1 in N.D.C. Corour Diva	Grey	
P-68-FSC-BRN	With 1 in. N.P.S. Screw Plug	Brown	

New MopTite™ Covers exceed UL watertight requirements for 514A, 514C

Cat. No.	Description	Colour	Std. Ctn.
P-68-FSC-BGE	With 1 in N.D.C. Conour Dive	Beige	4
P-68-FSC-BLK	With 1 in. N.P.S. Screw Plug	Black	
P-68-DRC-GRY		Grey	
P-68-DRC-BRN	For Dunlay December	Brown	
P-68-DRC-BGE	For Duplex Receptacle	Beige	
P-68-DRC-BLK		Black	



#### MopTite<sup>™</sup> Cover Plates for 68 and 600 Series

- · Polished brass finish
- Furnished complete with sealing gasket and 8-32 x 7/16 in. brass screws
- 4 in. outside diameter



P-60-1/2 1/2 in. N.P.S. plug



P-60-3/4 3/4 in. N.P.S. plug



P-60-1-1/4 1-1/4 in. N.P.S. plug



P-60-DS\* Hinged lift lids



P-60-DU\* Duplex 1-7/16 in. lid



P-60-1

1 in. N.P.S. plug

P-60-2\* 2 in. dia. plug



P-60-2-5/8\* 2-5/8 in. dia. plug



P-60-1/2-2\* 1/2 in. & 2 in. dia. plugs




P-60-3/4-2\* 3/4 in. & 2 in. dia. plugs





P-60-DR\* P-60-GFCI\* For GFCI Devices Duplex lift lid



\*Also includes steel seating plate for receptacles

Cat. No.	Description	Finish	Std. Ctn.
P-60-1/2	1/O in N.D.C. Diver Cine	Brass	
P-60-1/2-AL	1/2 in. N.P.S. Plug Size	Aluminum	
P-60-3/4	2/4 in N.D.C. Diver Cine	Brass	
P-60-3/4-AL	3/4 in. N.P.S. Plug Size	Aluminum	
P-60-1	1 in M.D.C. Dlug Ciro	Brass	
P-60-1-AL	1 in. N.P.S. Plug Size	Aluminum	
P-60-1-1/4	1 1/A in N.D.C. Dlug Ciro	Brass	
P-60-1-1/4-AL	1-1/4 in. N.P.S. Plug Size	Aluminum	
P-60-2	2 in Diameter Plus Cite	Brass	
P-60-2-AL	2 in. Diameter Plug Size	Aluminum	4
P-60-2-5/8	2 E/0 in Diameter Plus Cite	Brass	
P-60-2-5/8-AL	2-5/8 in. Diameter Plug Size	Aluminum	
P-60-1/2-2	1/2 2 in Diameter Plus Cite	Brass	
P-60-1/2-2-AL	1/2 – 2 in. Diameter Plug Size	Aluminum	
P-60-3/4-2	2/4 2 in Diameter Plus Cite	Brass	
P-60-3/4-2-AL	3/4 – 2 in. Diameter Plug Size	Aluminum	
P-60-DR	With Duplex Lift Lid	Brass	
P-60-DS	For Duploy with Individual Lift Lide	Brass	
P-60-DS-AL	For Duplex with Individual Lift Lids	Aluminum	
P-60-DU	With True 1 7/1C in Divine for Dunlay	Brass	
P-60-DU-AL	With Two 1-7/16 in. Plugs for Duplex	Aluminum	
P-60-GFCI	For CECI Davisos	Brass	
P-60-GFCI-AL	For GFCI Devices	Aluminum	

68P-FL or 68P-FL-AL required to attach cover plates to 68-P floor box New MopTite™ Covers exceed UL watertight requirements for 514A, 514C For replacement parts, please refer to pages C86 - C87





(I) (II)

#### **Dual-Voltage Kits for 68-P Nonmetallic Series**



- Voltage divider has easy-cut score lines to accommodate concrete depths of 3 to 6 inches
- Faceplate has removable data plates and can accommodate GFCl or standard duplex receptacles
- Kit comes equipped with 4 standard keystone-size openings in the data plates. Other styles available include openings sized for Ortronics, Avaya, Panduit and Hubbell®
- MopTite™ cover uses a "Snap-Lock" to close the lid. No screws to turn... just push down the lid and it snaps in place.
   The cover uses a factory-installed gasket and exceeds all UL scrub-water exclusion requirements for carpet, wood and tile floors
- MopTite<sup>™</sup> cover available in solid brass or aluminum
- Includes everything required for a standard installation (68P floor box, data jacks and receptacles not included)



Cat. No.	Description		
68P-DV-KIT-BRS	With Brass Cover		
68P-DV-KIT-AL	With Aluminum Cover	1	
<b>68P-DV-DP-ORT</b> * Ortronics Data Plate to Accommodate 2 Jacks			
68P-DV-DP-PAN*	PANDUIT Data Plate to Accommodate 2 Jacks	s 10	
68P-DV-DP	Standard Data Plate to Accommodate 4 Keystone Jacks	10	

\*CSA not Certified. Keystone data plates come standard with the kit. Other style data plates are available from T&B and can be ordered separately