

Metal PlugTrak® Series

Available in Standard, Isolated Ground (IG), Tamper-Resistant (TR) and USB (U) versions.



	Amp Circuits	Single Recept.	USB Ports	Receptacle Spacing (in.)	Color	
					Ivory	Gray
3 Foot	15 Single	6	—	6	HBL20GB306IV	HBL20GB306GY
	15 IG/Single	6	—	6	HBL20IG306IV	HBL20IG306GY
	15 TR/Single	6	—	6	HBL20GB306IVTR	HBL20GB306GYTR
	15 USB/Single	2	2	12	HBL20GB312UIV	—
	20 Single	6	—	6	HBL24GB306IV	HBL24GB306GY
	20 TR/Single	6	—	6	HBL24GB306IVTR	HBL24GB306GYTR
5 Foot	15 Single	10	—	6	HBL20GB506IV	HBL20GB506GY
	15 Single	5	—	12	HBL20GB512IV	HBL20GB512GY
	15 Two	5	—	12	HBL20GBA512IV	HBL20GBA512GY
	15 IG/Single	5	—	12	HBL20IG512IV	HBL20IG512GY
	15 TR/Single	5	—	12	HBL20GB512IVTR	HBL20GB512GYTR
	20 Single	10	—	6	HBL24GB506IV	HBL24GB506GY
	20 Single	5	—	12	HBL24GB512IV	HBL24GB512GY
	20 Two	5	—	12	HBL24GBA512IV	HBL24GBA512GY
6 Foot	15 Single	12	—	6	HBL20GB606IV	HBL20GB606GY
	15 Single	8	—	9	HBL20GB609IV	HBL20GB609GY
	15 Single	6	—	12	HBL20GB612IV	HBL20GB612GY
	15 Single	4	—	18	HBL20GB618IV	HBL20GB618GY
	15 Two	8	—	9	HBL20GBA609IV	HBL20GBA609GY
	15 Two	6	—	12	HBL20GBA612IV	HBL20GBA612GY
	15 Two	4	—	18	HBL20GBA618IV	HBL20GBA618GY
	15 IG/Single	12	—	6	HBL20IG606IV	HBL20IG606GY
	15 USB/Single	4	4	12	HBL20GB612UIV	—
	20 Single	12	—	6	HBL24GB606IV	HBL24GB606GY
	20 Single	6	—	12	HBL24GB612IV	HBL24GB612GY
	20 Single	4	—	18	HBL24GB618IV	HBL24GB618GY
	20 Two	6	—	12	HBL24GBA612IV	HBL24GBA612GY
	20 Two	4	—	18	HBL24GBA618IV	HBL24GBA618GY



Portable	Amp Circuits	Length (in.)	Cord Length (ft.)	Single Recept.	USB Ports	Color	
						Ivory	Gray
	15 Single	40	6	6	—	HBL20C215IV	HBL20C215GY
	15 USB/Single	40	6	4	2	HBL20C215UIV	—
	15 Single	64	6	10	—	HBL20C315IV	HBL20C315GY

Note: IG = Isolated Ground, TR = Tamper-Resistant and U = USB.
 Hubbell Metal PlugTrak is supplied with two HBL2010BIV/GY blank end fittings and one HBL2001C coupling. Catalog number suffix "IV" for ivory finish and "GY" for gray finish. Outlets match raceway color. "IG" Isolated ground receptacles have orange triangles. Portable PlugTrak includes 15A circuit breaker.

Dimensions in Inches (mm)

	Description	Color	Catalog Number
Boxes	1-Gang Device Box	Ivory Gray	HBL2048IV HBL2048GY
	2-Gang Device Box	Ivory Gray	HBL20482IV HBL20482GY
Elbows and Tees	External Elbow	Ivory Gray	HBL2018CIV HBL2018CGY
	Flat Elbow	Ivory Gray	HBL2011IV HBL2011GY
	Tee	Ivory Gray	HBL2015IV HBL2015GY
End Fittings	Entrance End Fitting	Ivory Gray	HBL2010A2IV HBL2010A2GY
	Large Entrance End Fitting	Ivory Gray	HBL2010A3IV HBL2010A3GY
	Blank End Fitting	Ivory Gray	HBL2010BIV HBL2010BGY
	Cover Clip	Ivory Gray	HBL2006IV HBL2006GY
Fittings	Supporting Clip	Steel**	HBL2003SC*
	Coupling	Steel**	HBL2001C
	Internal Corner Coupling	Steel**	HBL2017TC

Note: *Support clip HBL2003SC for supporting Portable Metal PlugTrak only.
 **Galvanized Steel.
 See pages T-10 and T-11 for additional information.